


TOLON

Laundry Solutions
in the Line of Orange



Washer Extractors TWE 60 - 110

OPTIONS

- Dual heating (electric & steam) selectable through the control (not on TWE 110)
- Forward tilting
- Extra inlet valve for soft water
- Pneumatic inlet valves for faster filling, standard on TWE 110
- Pneumatic steam valve on TWE 60, standard on TWE 110
- Second drain valve for water recovery
- Weighing cells to measure amount of linen and reduce the water, energy and detergent consumption accordingly

STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid or powder detergent in 3 or 6 compartment frontal dispenser (available end 2017)
Now soap dispenser on side with 5 compartments.
- Standard equipped for automatic soap dosing
- Drum and tub, as well as the entire cabinet made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" (TWE 60) or 4" (TWE 110) drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 60	TWE 110
Dry load	lb	132	243
Performance	lb/h	198	364
Cycle time	min	40-45	40-45
DRUM			
Drum diameter	inches	43,3	51,2
Drum depth	inches	24	32,7
Drum volume	gal	20,4	38,9
Wash speed	rpm	34	29
Extraction speed	rpm	770	720
G-Force		360	360
DOOR			
Door opening ø	inches	22	27
HEATING			
Electric	BTU	142,488	n/a
Steam	BTU	66,700	66,700
ELECTRIC			
Electric consumption*	HP/h	8	n/a
Motor	HP	15	30
STEAM			
Steam valve connection ø	DN-BSP	25-1"	40- 1½"
Steam pressure	psi	29-87	29-87
Steam consumption	lb/cycle	62	110
AIR			
Air connection ø	inches	optional / 0,31	0,39
WATER			
Inlet valve connection ø	DN-BSP	2 x 25-1"	2 x 50-2"
Water inlet (detergent) ø	DN-BSP	1 x 25-1"	1 x 25-1"
Water pressure	psi	29-58	29-58
Water flow	gal/min	40	130
Water consumption*	cold gal/cycle	110	200
	hot gal/cycle	30	60
Drain valve connection ø (outer)	inches	3	3
Drain flow	gal/min	60	60
PROGRAMMABLE CONTROL			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
DIMENSIONS			
Standard WxDxH	inches	65x62x76	73x77x82
Tilting WxDxH	inches	71x63x85	78x79x89
Packing WxDxH	inches	67x65x82	77x89x88
Packing Tilting WxDxH	inches	75x69x90	83x91x95
WEIGHT			
Net	lb	4079	9193
Gross	lb	4134	9303
SOUND LEVEL			
	db(A)	67-77	70-77

* Consumption figures based on ,Eco 60°C' program (main wash, 2 rinses)